## **PopPack**



## 96631587 POPPACK LED 9000-840 PIR L1500



## **PopPack**


Batten LED luminaire with detachable LED engine. Electronic, fixed output control gear. Body: coated, formed steel, white (RAL9016). End caps: injection moulded polycarbonate, white. Diffuser: textured opal acrylic. Electrical connection via 2 x (3 x 2 x 2.5mm²) terminal blocks. Including pre-wired PIR sensor with switch ON/OFF functionality. Enabled control of slave luminaire from one master luminaire equipped with PIR sensor by means of hard wiring. 3 core wiring sufficient for the through wiring of the products, max. load per circuit = 2A. Complete with 4000K LED.

Dimensions: 1449 x 60 x 74 mm Luminaire input power: 63.6 W Luminaire luminous flux: 9100 lm Luminaire efficacy: 143 lm/W


Weight: 1.7 kg



TLG POPL F PDB SENS.jpg



TLG\_POPL\_M\_LD1.wmf



TLG\_SP\_0043756.ldt

Lamp position: STD - standard

Light Source: LED

Luminaire luminous flux\*: 9100 lm Luminaire efficacy\*: 143 lm/W Colour Rendering Index min.: 80

Ballast: 1 x 28003378 LC 65/200-350/210 flexCC lp

SNC3

LOR: 1,00 ULOR: 0,17 DLOR: 0,83

Correlated colour temperature: 4000 Kelvin Chromaticity tolerance (initial MacAdam): 3

Rated median useful life\*: L80 50000h at 25°C

Luminaire input power\*: 63.6 W Power factor = 0.95

Dimming: FO

Maintenance category: D - Enclosed IP2X

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.