ANNA VARIO Q596 3000 830/35/40 96634030

Recessed LED panel

Recessed LED panel UGR<19 with adjustable color temperature of 3000K, 3500K or 4000K by switch directly on luminaire. Gentle, soft and glare-free lighting for office applications with opal diffuser made of TpB rated PET for fully homogenous illumination and aluminium frame. Luminaire input power: 29 W Lifetime of 50.000 h before luminous flux is reduced to 80 % of the initial value. Chromaticity tolerance (initial MacAdam): 4. Total luminous flux: 3000 lm, Luminaire efficacy: 104 lm/W (4000K). Colour rendering Ra > 80,Tool-free installation (piano key terminal for up to 2.5 mm² wires). External connector box enabling loop-in loop-out wiring. Flicker free. Suitable for lay-in installation, suspension and surface mounting.Dimensions: 596 x 596 x 60 mm weight: 2.22 kg

TE_ANNA_F_600_persp.jpg



TE_ANNAVARIO_M_596.wmf

Light Distribution STD - standard



TE_ANNA_VARIO_Q596_3000_840.ldt

- Light Source: LED
- Luminaire luminous flux*: 3003 lm
- Luminaire efficacy*: 104 lm/W
- Colour Rendering Index min.: 80
- Correlated colour temperature: 3000-4000 Kelvin
- Chromaticity tolerance (initial MacAdam): 4
- Rated median useful life*:
  L80 50000h at 25°C
- Ballast: 1x LED_Con
- Luminaire input power*: 29 W Power factor = 0.95
- Dimming: Fixed output

All values marked with an * are rated values. Luminous flux and connected electrical load are subject to an initial tolerance of +/- 10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

IEC EN 60598-1 RG 0 | RoHS | IP20 IP44 | IK03 | 650°C | Ta -20 +40

We reserve the right to make technical changes without prior notice. 24.06.2021 © ThornEco