

Calinor LED Polycarbonate

Supplied c/w Integral Driver

420



5 - 12 Metres
10 Seconds - 8 Minutes
3 Lux - PC Off
Detection Angle - 120°



ACALED10



ACALED10/PIR



ACALED20




ACALED20/PIR




AMFLSA
Floodlighting Spike
Accessory


- Compact and economic polycarbonate LED floodlight
- Only suitable for semi commercial applications
- Warm and Cool white options
- 10W LED ideal for halogen replacement 20W LED exceeds performance of 20W HQI
- Polished faceted reflector and textured glass for optimum performance
- Pre-wired with 1 metre of rubber insulated cable for ease of installation (500mm for 10W)
- Polycarbonate spike accessory (up to 50W versions only) allowing installation into lawn and garden applications
- PIR versions complete with manual override facility
- LED lifespan L70 20,000 hours
- Non-dimmable




ACALED10



ACALED10/PIR



ACALED20



ACALED20/PIR

	Code	Lamp	Description	Windage
Standard	ACALED10	LED	10W - Cool White	0.02
PIR	ACALED10/PIR	LED	10W c/w PIR - Cool White	0.04
Standard	ACALED20	LED	20W - Cool White	0.03
PIR	ACALED20/PIR	LED	20W c/w PIR - Cool White	0.05

Standard	ACALED10/WW	LED	10W - Warm White	0.02
PIR	ACALED10/WW/PIR	LED	10W c/w PIR - Warm White	0.04
Standard	ACALED20/WW	LED	20W - Warm White	0.03
PIR	ACALED20/WW/PIR	LED	20W c/w PIR - Warm White	0.05

Accessory	AMFLSA	Floodlighting Spike Accessory		
-----------	--------	-------------------------------	--	--

LED Information

Total (Watts)	10W 20W	
Lumens Delivered	Cool White	Warm White
10W	942lm	892lm
20W	1924lm	1807lm
Lm/W 10W	94lm	89lm
Lm/W 20W	96lm	90lm
CRI	Ra 80	
CCT	4000K 3000K	
Input	230V	
Hertz	50Hz	
Operating Temp	-15°C to 40°C	