



AERMLED3/60/DL

Endurance LED Recessed Panel - 600 x 600 Daylight 30W



Features

High performance maintenance free LED Panel

Tpa as standard

UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort

30W panel outperforms 3x14W T5

Cool white and warm white options

White anodised aluminium frame for visual compatibility with ceiling grid

Low glare and even light distribution for multiple applications

Panel Pod Self-test emergency option

Panel Pod sensor option

Surface mounting frame option

Supplied c/w Philips LED driver

LED Lifespan L70 60,000 hours

General Information

Lamp Type	LED
Colour / Finish	White
IP Rating	IP44
Class Protection	II
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Diffuser Rating	Tp(a)
LED Life	L70 60,000h
Warranty (Years)	5
CE Mark	Yes
Length (mm)	595
Width (mm)	595
Depth (mm)	10

Technical Information

Wattage	30W
Lumens Delivered	2938lm
Lm/W	101lm
CRI	Ra80
CCT	6000K
Input	230V
Hertz	50Hz
Operating Temp	-20°C to 40°C

Datasheet generated from <https://www.electrika.com> last updated Friday, June 28, 2019 12:03:19 PM

