

Vaste AC LED

AC LED (No Driver Required)

410



6 Metres
5 Seconds - 8 Minutes
10 - 2000 Lux



AVFLED10



AVFLED10/PIR




AVFLED20




AVFLED30


- Modern architectural slim die-cast LED floodlight
- 10W ideal for halogen replacement
- 20W LED exceeds performance of 20W HQI
- 30W comparable light output to 35W HQI
- Die-Cast construction and heat sink design providing optimised thermal characteristics for optimum LED life and performance
- Graphite textured paint finish
- Pre-wired with 1 metre of rubber insulated cable for ease of installation
- Polycarbonate spike accessory (up to 50W versions only) allowing installation into lawn and garden applications
- PIR versions complete with manual override facility
- LED lifespan L80 60,000 hours
- Non-dimmable



AVFLED10



AVFLED20



AVFLED30

	Code	Lamp	Description	Windage
Standard	AVFLED10	LED	10W - Cool White	0.01
PIR	AVFLED10/PIR	LED	10W c/w PIR - Cool White	0.01
Standard	AVFLED20	LED	20W - Cool White	0.04
Standard	AVFLED30	LED	30W - Cool White	0.02

Option	/PC	Electronic Photocell (50W only)
---------------	------------	---------------------------------

Accessory	AMFLSA	Floodlighting Spike Accessory
------------------	---------------	-------------------------------

LED Information

Total (Watts)	10W
	20W
	30W

Lumens Delivered	
10W	938lm
20W	1800lm
30W	2899lm

Lm/W 10W	94lm
Lm/W 20W	90lm
Lm/W 30W	97lm

CRI	Ra 80
-----	-------

CCT	4000K
-----	-------

Input	220-240V
-------	----------

Hertz	50/60Hz
-------	---------

Operating Temp	-20°C to 25°C
----------------	---------------