

# Zion LED Polycarbonate

Supplied c/w Integral Driver

- Compact and economic polycarbonate LED floodlight
- Only suitable for semi commercial applications
- 30W LED comparable light output of 35W HQI
- 50W LED exceeds performance of 70W HQI
- Polished faceted reflector and textured polycarbonate for optimum performance
- Bracket design allows installation without removing mounting bracket
- Pre-wired with 1 metre of rubber insulated cable for ease of installation
- Polycarbonate spike accessory (up to 50W versions only) allowing installation into lawn and garden applications
- PIR versions complete with manual override facility
- LED lifespan L70 52,000 hours
- Non-dimmable



10 Metres Fixed  
8 Seconds - 12 Minutes  
0 - 1000 LUX  
Detection Angle - 120°



AZILED30



AZILED30/PIR




AZILED50




AZILED50/PIR



AMFLSA  
Floodlighting Spike  
Accessory



AZILED30 - AZILED30/PIR



AZILED50 - AZILED50/PIR

## LED Information

Total (Watts)	30W	
	50W	
Lumens Delivered	Cool White	Warm White
30W	2614lm	2415lm
50W	4698lm	4198lm
Lm/W 30W	84lm	78lm
Lm/W 50W	94lm	84lm
CRI	Ra 70	
CCT	4000K	
	3000K	
Input	230V	
Hertz	50Hz	
Operating Temp	-10°C to 40°C	

	Code	Lamp	Description	Windage
<b>Standard</b>	<b>AZILED30</b>	LED	30W - Cool White	0.04
<b>PIR</b>	<b>AZILED30/PIR</b>	LED	30W c/w PIR - Cool White	0.04
<b>Standard</b>	<b>AZILED50</b>	LED	50W - Cool White	0.05
<b>PIR</b>	<b>AZILED50/PIR</b>	LED	50W c/w PIR - Cool White	0.05
<b>Standard</b>	<b>AZILED30/WW</b>	LED	30W - Warm White	0.04
<b>PIR</b>	<b>AZILED30/WW/PIR</b>	LED	30W c/w PIR - Warm White	0.04
<b>Standard</b>	<b>AZILED50/WW</b>	LED	50W - Warm White	0.05
<b>PIR</b>	<b>AZILED50/WW/PIR</b>	LED	50W c/w PIR - Warm White	0.05
<b>Accessory</b>	<b>AMFLSA</b>		Floodlighting Spike Accessory	



Warrington: +44 (0) 1942 433333  
Belfast: +44 (0) 2890 773750

