



# Coreline Highbay Gen4

## BY120P G4 LED100S/865 PSU NB

865 cool daylight - Power supply unit - Narrow beam - Gray

Following the success of the previous generation CoreLine High-bay, the upgrade to a new generation further improves performance with new innovation design and provides higher efficiency, longer lifetime (to further improve the total cost of ownership), and optional DALI dimming for even further savings. Designed as a replacement for HPI 250/400 W luminaires, CoreLine High-bay G4 offers customers all the benefits of LED lighting – fresh light quality, longer service lifetime, reduced energy consumption and less maintenance – from a trusted manufacturer. At the same time, it delivers clear benefits for the installer too. The luminaire can be installed on the existing grid; electrical connection is straightforward – there is no need to open the luminaire for installation or servicing; and being smaller and lighter than conventional luminaires, it is very easy to handle

### Product data

General Information			
Beam angle of light source	55 °	Cable	Cable 0.3 m with connector 3-pole
Light source color	865 cool daylight	Protection class IEC	Safety class I
Light source replaceable	No	Glow-wire test	Temperature 650 °C, duration 30 s
Number of gear units	1 unit	Flammability mark	For mounting on normally flammable surfaces
Driver/power unit/transformer	Power supply unit	CE mark	CE mark
Driver included	Yes	ENEC mark	-
Optic type	Narrow beam	Warranty period	5 years
Luminaire light beam spread	55°	Constant light output	No
Control interface	-	Number of products on MCB of 16 A type B	8
Connection	Connection unit 3-pole	RoHS mark	RoHS mark

# Coreline Highbay Gen4

Unified glare rating CEN	22
--------------------------	----

## Operating and Electrical

Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	- W
Inrush current	54 A
Inrush time	0.65 ms
Power Factor (Min)	0.95

## Controls and Dimming

Dimmable	No
----------	----

## Mechanical and Housing

Housing Material	Aluminum
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	-
Optical cover/lens finish	Clear
Overall height	95 mm
Overall diameter	385 mm
Color	Gray

## Approval and Application

Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [ 2 J reinforced]

## Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	10000 lm
Luminous flux tolerance	+/-10%

Initial LED luminaire efficacy	145 lm/W
Init. Corr. Color Temperature	6500 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.307, 0.323 SDCM <5
Initial input power	69 W
Power consumption tolerance	+/-10%

## Over Time Performance (IEC Compliant)


Control gear failure rate at median useful life	5 %
50000 h	
Median useful life L70B50	70000 h
Lumen maintenance at median useful life*	L80
50000 h	

## Application Conditions


Ambient temperature range	-30 to +45 °C
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Yes

## Product Data

Full product code	871016333567400
Order product name	BY120P G4 LED100S/865 PSU NB
EAN/UPC - Product	8710163335674
Order code	911401575251
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401575251
Net Weight (Piece)	3.300 kg



## Dimensional drawing



CoreLine High-bay BY120P/BY121P

