ECO SERIES LED SLIM RECESSED PANEL LIGHT

40W 600 x 600mm LED Panel - White Trim

4000K , 6000K CODE

110-230V AC 50-60Hz INPUT VOLTAGE 372PCS LED SMD Epistar LED QTY

Includes non-dimmable driver DRIVER

40W WATTAGE 3400Lm LUMEN

6000k/4000k/3000k COLOUR TEMP

>80 CRI White FINISH

595 x 595 x 9mm SI7F

30,000hrs LIFETIME

4 X 18W (72W) Fluorescent ALTERNATIVE TO

ENERGY SAVING















ACCESSORIES

Description Code

Universal 3 hour emergency pack T401 Suspension kit for LED panels T405

Surface Mount frame for 600 x 600 LED panels T402

Features & Benefits

- Ideal replacement for 600 x 600mm fluorescent fittings
- 595 x 595mm size for direct and quick retro fitting
- · Output outperforms traditional fluorescents
- · Even light distribution on walls and ceilings
- · Aids LG3 and LG7 compliance
- · Emergency and dimmable versions available

- Slim Profile
- · Save 50-70% on energy costs
- · Instant start, maintenance free
- · Free from mercury and other hazardous materials
- Long Life − 30,000 hours
- · Low heat output





