

LED SLIM RECESSED PANEL LIGHT

40W 600 x 600mm LED Panel - White Trim

CODE	4000K , 6000K
INPUT VOLTAGE	110-230V AC 50-60Hz
LED QTY	372PCS LED SMD Epistar
DRIVER	Includes Lifud non dimmable driver
WATTAGE	40W
LUMEN	3800Lm
COLOUR TEMP	6000k/4000k/ 3000k
CRI	>80
FINISH	White
SIZE	595 x 595 x 9mm
LIFETIME	30,000hrs
ALTERNATIVE TO	4 X 18W (72W) Fluorescent
ENERGY SAVING	50%



LIFUD Driver In

40 Watt	30,000 Hours	3800L	4000/5500 Kelvins	5 Year Warranty	CE EMC
---------	--------------	-------	-------------------	-----------------	--------

ACCESSORIES

Code	Description
T401	Universal 3 hour emergency pack
T405	Suspension kit for LED panels
T402	Surface mount frame for 600 x 600 LED panels

Features & Benefits

- Ideal replacement for 600 x 600mm fluorescent fittings
- 595 x 595mm size for direct and quick retro fitting
- Output outperforms traditional fluorescents
- Even light distribution on walls and ceilings
- Aids LG3 and LG7 compliance
- Emergency and dimmable versions available
- Slim Profile
- Save 50-70% on energy costs
- Instant start, maintenance free
- Free from mercury and other hazardous materials
- Long Life – 30,000 hours
- Low heat output

