DOWNLIGHT LED 200 35 W 4000 K WT

LEDVANCE DOWNLIGHT LED | LED downlight luminaires

Areas of application

- Direct replacement for luminaires with compact fluorescent lamps
- General illumination
- Public areas
- Stairways
- Corridors
- Foyers
- Shops

Product benefits

- High luminous efficacy
- Direct replacement for compact fluorescent lamp downlights
- Energy savings up to 60 % (compared to luminaires that use CFL lamps)
- Very homogenous light
- Functional design
- Easy installation with fast connection
- External driver for extended flexibility (compatible with selected DALI drivers)

Product features

- Diameter of required ceiling cut-out: 150 mm or 200 mm (depending on version)
- Type of protection: IP20
- Lifetime (L70/B50): up to 30,000 h (at 25 °C)
- Certificates: CE, CB, TUEV SUED

© 2017, LEDVANCE GmbH. All rights reserved.

Technical data

Electrical data

Operating mode	Electronic control gear (EVG)
Nominal wattage	35.00 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	4000 K
Luminous flux	3325 lm
Light color (designation)	Cool White
Color rendering index Ra	>80

Light technical data

Beam angle	100.00 °

Dimensions & weight



Diameter	220.0 mm
Height	67.0 mm

Colors & materials

Body material	Aluminum
Product color	White
Cover material	Polymethylmethacrylate (PMMA)

Temperatures & operating conditions

Ambient temperature range	-20...45 °C

© 2017, LEDVANCE GmbH. All rights reserved.

Capabilities

Dimmable	No

Certificates & standards

Protection class	II
Type of protection	IP20
Standards	CE/CB/TÜV SÜD/EAC/ROHS
Energy efficiency class	A

Equipment / Accessories

- Recommended DALI driver OTi DALI 15/220...240/1A0 LT2 (4052899324879)

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075016347	DOWNLIGHT LED 200 35 W 4000 K WT	Shipping carton box 8	470 mm x 470 mm x 250 mm	55.23 dm^3	11435.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For Guarantee see

- www.osram.com/www.ledvance.com/guarantee

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2017, LEDVANCE GmbH. All rights reserved.