

CoreLine Panel

RC125B LED345/830 PSU W60L60 NOC

LED Module, system flux 3400 lm - 830 warm white -
Power supply unit - Width 0.60 m, length 0.60 m - Non
office compliant version

Whether for a new building or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. The new CoreLine Panel range of LED products can be used to replace functional luminaires in general lighting applications. Both Non-Office Compliant (NOC) version and Office Compliant version (OC) are now available. The process of selecting, installing and maintaining is so easy – it's a simple switch.

Product data

• General Information

Lamp family code	LED Module, system flux 3400 lm
Light source color	830 warm white
Light source replaceable	No
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Luminaire light beam spread	110°
Connection	Push-in connector and pull relief
Protection class IEC	Safety class II
Flammability mark	For mounting on normally flammable surfaces
Safety device	SC [Safety cable]
Type description	Non office compliant version
CE mark	CE mark
ENEC mark	-
UL mark	-
Product family code	RC125B

• Light Technical

Luminous flux tolerance	+/-5%
-------------------------	-------

• Operating and Electrical

Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz

• Controls and Dimming

Dimmable	No
----------	----

• Mechanical and Housing

Geometry	Width 0.60 m, length 0.60 m
Housing Material	Steel
Gear tray material	Plastic

• Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]

• Initial Performance (IEC Compliant)

Initial luminous flux	3400 lm
Initial LED luminaire efficacy	83 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.44, 0.41) SDCM <5
Initial input power	41 W

• Over Time Performance (IEC Compliant)

Median useful life L90B50	15000 h
Median useful life L80B50	30000 h
Median useful life L70B50	50000 h
Driver failure rate at 5000 h	0.38 %

PHILIPS

CoreLine Panel


• Application Conditions

Ambient temperature range	+10 to +40 °C
Suitable for random switching	Yes (relates to presence/ movement detection and daylight harvesting)


• Product Data

Full product code	871869607032100
Order product name	RC125B LED34S/830 PSU W60L60 NOC
EAN/UPC - Product	8718696070321

Order code	910503910107
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	910503910107
Net Weight (Piece)	4.100 kg



Dimensional drawing



© 2016 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2016, April 12
data subject to change