

SPOT


LED Emergency Down Light



Product Features

- Open area/corridor 2 lenses included and replaceable
- Open area 130lm, corridor 120lm
- LiFePO4 battery
- Driver + battery foldable for shallow ceiling voids

DIMENSIONS



Model No.	SSPO
Voltage	AC220-240V 50/60Hz
Power	7W
Lumen	Open area - 130lm Corridor - 120lm
EM Duration	3 hours
Color Temp	6500K
Ambient Temp	5-45°C
Function	Non-Maintained Standard/Self Test
Battery	LiFePO4 3.2V 1500mAh
Dimension	Lamp head: Ø50x14.5mm Converter: 26.0x22.5mm
IP Grade	IP20
Material	PC
Mounting	Recessed mounting
Certificate	TUV CB/CE/RoHS
Warranty	4 years(battery 2 years)



SPITFIRE PRO


LED Emergency Down Light



Product Features

- Open area/corridor 2 lenses included and replaceable
- Open area 280lm, corridor 230lm
- LiFePO4 battery
- With D14.5mm large ring
- Australia D40 Class

DIMENSIONS



Model No.	SSPP
Voltage	AC220-240V 50/60Hz
Emergency Power	<3W
Lumen	Open area - 280 lumens Corridor - 230 lumens
EM Duration	3 hours
Color Temp	6500K
Ambient Temp	5-45°C
Function	Non-Maintained Standard/Self Test
Battery	LiFePO4 6.4V 1500mAh
Dimension	Lamp head: Ø26x14.5mm Converter: 20.6x13.2mm Big ring: Ø 14.5mm
IP Grade	IP20
Material	PC
Mounting	Recessed mounting
Certificate	TUV CB/CE/RoHS
Warranty	4 years(battery 2 years)

