PopPack LED

PP6500D / 96242251 POPPACK LED6500-840 HFI L1800

LED 60W LED_POPR_6550	IP20	IK03	⏚	CE	650°C	T_a -20 +25	

PopPack LED

Batten LED luminaire with replaceable 6500lm light engine. Electronic, DALI / DSI digital dimmable control gear. Body: coated, formed steel, white (RAL9016). End caps: injection moulded polycarbonate, white. Diffuser: textured opal acrylic. Electrical connection via 6 x 2 x 2.5mm² terminal block. Complete with 4000K LED

Dimensions: 1795 x 60 x 74 mm
Total power: 60 W
Luminaire luminous flux: 6550 lm
Luminaire efficacy: 109 lm/W
Weight: 2 kg

TLG_POPR_F_LEDPDB.jpg



TLG_POPR_M_LED.wmf



TLG_SP_0042054.ldt

Lamp position: STD - standard
Light Source: LED
Luminaire luminous flux*: 6550 lm
Luminaire efficacy*: 109 lm/W
Lamp efficacy: 109 lm/W
Colour Rendering Index min.: 80
Correlated colour temperature*: 4000 Kelvin

Rated median useful life*: 50000h L70 at 25°C
Ballast: 1x HFI* Tridonic LCA
Luminaire input power*: 60 W Lambda = 0.95
Standby Power*: 0.5 W
Dimming: DALIDSI dimmable to 1%
Maintenance category: D - Enclosed IP2X
LOR: 1,00 ULOR: 0,17 DLOR: 0,83

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Colour temperature is subject to a tolerance of up to +/-150 Kelvin from the nominal value. Unless stated otherwise, the values apply to an ambient temperature of 25°C.
In most products the failure of one LED point causes no functional impairment to the lighting performance of the luminaire and is therefore no reason for complaint.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

PopPack LED

PP6500D / 96242251 POPPACK LED6500-840 HFI L1800



	C0	C90	C180	C270
0°	213	213	213	213
5°	213	212	213	212
10°	213	208	213	208
15°	212	202	212	202
20°	209	195	209	195
25°	206	185	206	185
30°	201	173	201	173
35°	197	159	197	159
40°	192	145	192	145
45°	186	130	186	130
50°	179	115	179	115
55°	172	99	172	99
60°	165	83	165	83
65°	157	66	157	66
70°	149	49	149	49
75°	140	34	140	34
80°	131	20	131	20
85°	121	8	121	8
90°	111	1	111	1
95°	101	1	101	1
100°	91	1	91	1
105°	81	1	81	1
110°	71	1	71	1
115°	62	1	62	1
120°	52	1	52	1
125°	41	1	41	1
130°	31	1	31	1
135°	22	1	22	1
140°	13	1	13	1
145°	5	1	5	1
150°	1	1	1	1
155°	0	0	0	0
160°	1	0	1	0
165°	0	0	0	0
170°	1	1	1	1
175°	0	0	0	0
180°	0	0	0	0

Light output ratio

LOR	100%
ULOR	17%
DLOR	83%
TFR	0.20 (17:83)
BUF	1.00

Glare Evaluation

X=4H, Y=8H	S=1.00H
Reflection factors	70/50/20
UGR transversal	<28
UGR axial	<25

Classification

LiTG	B31
EN	
BZ	BZ6
UTE	0.83 G+0.17 T
CIE Flux Codes	36 64 85 83 100

Utilization Factors

Room Reflectance Ceiling/Walls/Floor	Room Index 0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
70 / 50 / 20	49	56	63	68	76	81	84	89	93
70 / 30 / 20	41	48	55	61	68	74	78	84	88
70 / 10 / 20	35	42	49	54	62	68	73	79	84
50 / 50 / 20	45	52	59	63	70	74	78	82	85
50 / 30 / 20	38	45	52	57	64	69	73	78	81
50 / 10 / 20	33	40	47	51	59	64	68	74	78
30 / 50 / 20	43	49	55	59	64	69	72	76	78
30 / 30 / 20	36	43	49	53	60	64	67	72	75
30 / 10 / 20	32	38	44	49	55	60	64	69	73
0 / 0 / 0	28	33	39	43	49	53	57	61	64

According to CIBSE Technical Memorandum No. 5 1980

SHR Nom= 1.50
SHR Max= 1.75
SHR Max TR= 2.17

Photometric data file: TLG_SP_0042054.ldt

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting