

# PRODUCT DATASHEET

## LED FACADE UPDOWN 12 W 3000 K WT

**LEDVANCE OUTDOOR LED FACADE UPDOWN | Luminaires with classic shape and light outlet up and down**



---

### AREAS OF APPLICATION

- Outdoor
- Building facades
- Decorative illumination

---

### PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation
- Homogeneous light output

---

### PRODUCT FEATURES

- Very bright and functional outdoor LED luminaires
- Type of protection: IP54
- Die-cast aluminum housing
- Available in two housing colors: white and dark gray
- Diffuser made of clear glass



**TECHNICAL DATA**

## Electrical data

Nominal wattage	12.00 W
Nominal voltage	220...240 V
Nominal current	0.055 A
Power factor $\lambda$	>0.5
Mains frequency	50/60 Hz
Operating mode	Mains voltage

## Photometrical data

Luminous efficacy	60 lm/W
Luminous flux	710 lm
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	$\geq 80$
Standard deviation of color matching	<6 sdc <sub>m</sub>

## Light technical data

Beam angle	280.00 °
------------	----------

## Dimensions &amp; weight

Length	55.0 mm
Width	90.0 mm
Height	160.0 mm
Product weight	480.00 g

## Colors &amp; materials

Housing color	White
Product color	White
Body material	Aluminum
Cover material	Glass

## Temperatures &amp; operating conditions

Ambient temperature range	-20...40 °C
---------------------------	-------------

## Lifespan

Number of switching cycles	15000
Lifespan L70 at 25 °C	30000 h

## Additional product data

<b>Mounting location</b>	Wall
<b>Product remark</b>	Available from February 2018

### Capabilities

<b>Dimmable</b>	No
<b>Type of connection</b>	Terminal, 3-Pole (L, N, PE)
<b>LED module replaceable</b>	Not replaceable

### Certificates & standards

<b>Type of protection</b>	IP54
<b>Protection class</b>	I
<b>Protection class IK (shock resistance)</b>	IK06
<b>Standards</b>	CE
<b>Photobiological safety group</b>	RG 0

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

### LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075075078	LED FACADE UPDOWN 12 W 3000 K WT	Shipping carton box 6	245 mm x 240 mm x 195 mm	11.47 dm <sup>3</sup>	3193.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### REFERENCES / LINKS

For Guarantee see

- ▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.