

# PRODUCT DATASHEET

## HB DALI CLO 155 W 4000 K 115 DEG IP65 BK

**HIGHBAY DALI CONSTANT LUMEN 115DEG | LED high-bay luminaires with DALI interface and constant lumen function**



---

### AREAS OF APPLICATION

- Replacement for high bay luminaires with mercury vapor or metal halide lamps
- Warehouses
- Logistics halls
- Industry
- High ceiling (e.g. in shopping malls, airports, commercial buildings, lobbies)

---

### PRODUCT BENEFITS

- Same luminous flux over the luminaire's lifetime thanks to constant lumen function
- High compatibility thanks to DALI-2 certification
- DALI 2.0 interface for dimming and sensor operations
- Low flicker light thanks to special electronic control gear
- High luminous efficacy
- Easy electrical connection due to push button connector
- Energy savings of up to 90 % compared to conventional high bay luminaires
- 5 years guarantee

---

### PRODUCT FEATURES

- Pre-configured DALI driver included
- Luminous efficacy: up to 140 lm/W
- Type of protection: IP65
- Lifetime: up to 50,000 h



**TECHNICAL DATA**

Electrical data

Nominal wattage	125...155 W
Operating mode	Integrated LED driver
Nominal voltage	220...240 V
Power factor $\lambda$	$\geq 0.95$
Mains frequency	0/50/60 Hz

Luminaire control gear data

Output current	690 mA
ECG - Output ripple current	<10 %


Photometrical data

Color temperature	4000 K
Luminous efficacy	115...140 lm/W
Luminous flux	17500 lm
Standard deviation of color matching	<4 sdc <sub>m</sub>
Light color (designation)	Cool White
Color rendering index Ra	>80
Luminous efficacy of lamp in luminaire	115 lm/W

Light technical data

Beam angle	115 °
------------	-------

Dimensions & weight



Diameter	360.0 mm
Height	131.0 mm
Product weight	4985.00 g

## Colors &amp; materials

<b>Body material</b>	Aluminum
<b>Housing color</b>	Black
<b>Product color</b>	Black

## Temperatures &amp; operating conditions

<b>Ambient temperature range</b>	-30...50 °C
----------------------------------	-------------

## Additional product data

<b>Mounting type</b>	Surface
<b>Mounting location</b>	Ceiling / Wall
<b>Product remark</b>	Available from July 2018



## Capabilities

<b>Dimmable</b>	Yes
<b>Type of connection</b>	Terminal
<b>Constant lumen function</b>	Yes
<b>LED module replaceable</b>	Not replaceable

## Certificates &amp; standards

<b>Protection class IK (shock resistance)</b>	IK08
<b>Glow Wire Test according to IEC 695-2-1</b>	650 °C
<b>Photobiological safety group</b>	RG 0
<b>Protection class</b>	I
<b>Type of protection</b>	IP65
<b>Standards</b>	CE/CB/ENEC/TÜV SÜD/RoHS/EAC

Light Distribution



LDC typ cone

LDC typ polar

EQUIPMENT / ACCESSORIES

- Mounting hook included
- Mounting brackets and reflectors as separate accessory available

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075130654	HB DALI CLO 155 W 4000 K 115 DEG IP65 BK	Shipping carton box 1	400 mm x 400 mm x 200 mm	32.00 dm <sup>3</sup>	6346.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see  
 ▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.