

PRODUCT DATASHEET

DP HOUSING 1200 2x Lamp IP65

DAMP PROOF HOUSING | Damp-proof luminaire for T8 LED lamps



PRODUCT BENEFITS

- Prewired for easy installation of tubular AC LED lamps
- Robust housing
- Easy and quick installation
- 5 years guarantee

PRODUCT FEATURES

- Luminaire housing, available for 1 or 2 T8 LED lamps
- Type of protection: IP65
- Suitable for SubstiTUBE EM/UN and SubstiTUBE Connected



TECHNICAL DATA

Electrical data

| | |
|-----------------|-------------|
| Nominal voltage | 220...240 V |
| Mains frequency | 50/60 Hz |

Light technical data

| | |
|------------|----------|
| Beam angle | 105.00 ° |
|------------|----------|

Dimensions & weight



| | |
|----------------|-----------|
| Length | 1261 mm |
| Width | 103.0 mm |
| Height | 75.0 mm |
| Product weight | 1300.00 g |

Colors & materials

| | |
|----------------|--------------------|
| Body material | Polycarbonate (PC) |
| Product color | Gray |
| Housing color | Gray |
| Cover material | Polycarbonate (PC) |

Temperatures & operating conditions

| | |
|---------------------------|--------------|
| Ambient temperature range | -30...+40 °C |
|---------------------------|--------------|

Additional product data

| | |
|--------------------|---------|
| Mounting type | Surface |
| Mounting location | Ceiling |
| Equipped with lamp | No |

Capabilities

| | |
|----------|----|
| Dimmable | No |
|----------|----|

| | |
|--------------------|----------------|
| Type of connection | Screw terminal |
| Holder designation | G13 |

Certificates & standards

| | |
|---|---------------------------|
| Protection class IK (shock resistance) | IK08 |
| Protection class | I |
| Type of protection | IP65 |
| Luminaire with limited surface temperature, class "D" | No |
| Standards | CE/TÜV Rheinland/EAC/RoHS |

Logistical data

| | |
|------------------------------|-------------|
| Temperature range at storage | -20...80 °C |
|------------------------------|-------------|

EQUIPMENT / ACCESSORIES

- All required accessories included

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075312456 | Folding carton box 1 | 77 mm x 110 mm x 1265 mm | 1478.00 g | 10.71 dm ³ |
| 4058075312463 | Shipping carton box 6 | 1280 mm x 231 mm x 245 mm | 10141.00 g | 72.44 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

- ▶ www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.